

VALVOLINE INC -- NAPA MV MOTOR OIL SAE 10W30

=====

MSDS Safety Information

=====

FSC: 9150

MSDS Date: 02/28/1996

MSDS Num: CGRTT

LIIN: 00N053354

Product ID: NAPA MV MOTOR OIL SAE 10W30

MFN: 02

Responsible Party

Cage: GO029

Name: VALVOLINE INC

Box: 14000

City: LEXINGTON KY 40512

Info Phone Number: 606-357-7847

Emergency Phone Number: 800-274-5263

Published: Y

=====

Contractor Summary

=====

Cage: GO029

Name: VALVOLINE INC

Box: 14000

City: LEXINGTON KY 40512

Phone: (606) 268-7000

Cage: 72527

Name: VALVOLINE OIL

Address: 3499 DABNEY DRIVE

Box: 14000

City: LEXINGTON KY 40512

Phone: 606-357-7847/606-264-7000

=====

Ingredients

=====

Cas: 64742-65-0

RTECS #: PY8038501

Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC
(SEVERE SOLVENT-REFINING &/OR

% Wt: 83-93

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

Name: ING 1: HYDROTREATMENT); (ALIPHATIC PETROLEUM DISTILLATES)

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

RTECS #: 1010740DD

Name: DETERGENT/DISPERSANT ENGINE OIL PACKAGE

% Wt: 6-16

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

Cas: 68649-42-3

RTECS #: 1007710PT

Name: PHOSPHORODITHIOLIC ACID, O-O-D1 C1-14-ALKYL ESTERS, ZINC SALTS (2:1)
(ZDDP); (ZINC COMPOUNDS)

% Wt: 1.1

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

 Name: FIRST AID PROC: WATER, & GET MED ATTN IMMED. IF POSSIBLE, DO NOT
 LEAVE UNATTENDED. INHAL: IF SYMPTOMS DEVELOP,

Name: ING 5: IMMED MOVE AWAY FROM EXPOS & INTO FRESH AIR. SEEK IMMED MED
 ATTN; KEEP PERSON WARM & QUIET. IF PERSON IS

Name: ING 6: BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF BREATHING IS
 DIFFICULT, ADMINISTER OXYGEN.

Name: SPILL PROC: SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN
 COMPLETED. STOP SPILL AT SOURCE, DIKE

Name: ING 8: AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK.
 REMAINING LIQ MAY BE TAKEN UP ON SAND,

Name: ING 9: CLAY, EARTH, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND
 SHOVELED INTO CONTAINERS.

Name: VENT: (GENERAL &/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE
 BELOW PEL/TLV(S).
 =====

Health Hazards Data

=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE: EXPOS MAY CAUSE MILD IRRIT. SYMPS MAY INCL STINGING,
 TEARING & REDNESS. SKIN: EXPOS MAY CAUSE MILD SKIN IRRIT. PRLNGD/RPTD
 EXPOS MAY DRY SKIN. SYMPS MAY INCL REDNESS, BURNING, DRYING & CRACKING
 & SKIN BURNS. INGEST: SINGLE DOSE ORAL TO X IS LOW. SWALLOWING SM AMTS
 DURING NORM HNDLG IS NOT LIKELY TO(EFTS OF OVEREXP)

Explanation of Carcinogenicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: HLTH HAZ: CAUSE HARMFUL EFTS; SWALLOWING
 LG AMTS MAY BE HARMFUL. INHAL:EXPOS IS POSS UNDER CERTAIN CNDTNS OF HNDLG
 & USE (FOR EX, DURING HEATING, SPRAYING OR STIRRING). SYMPS ARE MRE
 TYPICALLY SEEN AT AIR CONCS EXCEEDING RECOMD EXPOS LIMS. SYMPS OF EXPOS:GI
 IRRIT (NAUS, VOMIT, DIARR), IRRIT (NOSE, THROAT, RESP(SUPDAT)

Medical Cond Aggravated By Exposure: PRE-EXISTING SKIN DISORDERS MAY BE
 AGGRAVATED BY EXPOSURE TO THIS MATERIAL. PRE-EXISTING LUNG DISORDERS, EG
 ASTHMA-LIKE CONDITIONS, MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

First Aid: EYES: IF SYMPS DEVELOP, MOVE INDIVIDUAL AWAY FROM EXPOS & INTO
 FRESH AIR. FLUSH EYES GENTLY W/WATER WHILE HOLDING EYELIDS APART FOR AT LEAST
 15 MIN. IF SYMPS PERSIST OR THERE IS ANY VISUAL DFCLTY, SEEK MED ATTN. SKIN:
 REMOVE CONTAMD CLTHG. WASH EXPOSED AREA W/SOAP & WATER. IF SYMPS PERSIST,
 SEEK MED ATTN. LAUNDRER CLTHG BEFORE REUSE. INGEST: DO NOT INDUCE VOMIT. GIVE
 ONE GLASS OF MILK OR
 =====

Handling and Disposal

=====

Spill Release Procedures: SM SPILL: ABSORB LIQ ON VERMICULITE, FLOOR ABSORB OR
 OTHER ABSORB MATL. LG SPILL: PVNT RUN-OFF TO SEWERS, STREAMS OR OTHR BODIES
 OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHS AS REQD THAT A SPILL HAS
 OCCURED. PERS NOT WEARING PROT EQUIP

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL,

STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: CNTNRS OF MATL MAY BE HAZ WHEN EMPTIED. SINCE EMPTIED CNTNRS RETAIN PROD RESIDUES (VAP, LIQ &/OR SOLID) ALL HAZ PRECS GIVEN IN MSDS MUST BE OBSERVED.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: 430F,221C

Extinguishing Media: REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE

EQUIPMENT (FP N). WATER/FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT & POSSIBLE ENDANGER LIFE OF FIREFIGHTER.

Unusual Fire/Explosion Hazard: NEVER USE WELDING/CUTTING TORCH ON/NEAR DRUM (EVEN EMPTY) BECAUSE PROD (EVEN JUST RESIDUE) CAN IGNITE EXPLO. DENSE SMOKE MAY BE GENERATED WHILE BURNING. (SUPDAT)

=====
Control Measures
=====

Respiratory Protection: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. HOWEVER, IF OIL MISTS ARE GENERATED ABOVE RECOMMENDED PEL/TLV OF 5 MG/M3 THEN A NIOSH APPROVED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL (CONSULT INDUSTRIAL HYGIENIST).

Ventilation: NOT REQD UNDER NORM CNDTNS OF USE. HOWEVER, IF UNUSUAL OPERATING CNDTNS EXIST, THEN PROVIDE SUFFICIENT MECH

Protective Gloves: RESISTANT SUCH AS NITRILE RUBBER.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N). WEAR NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: EXPLO HAZ: HAZ PRODS OF COMBUSTION: MAY FORM CARBON DIOXIDE & CARBON MONOXIDE, OXIDES OF SULFUR, NITROGEN & PHOSPHORUS, VARIOUS HYDROCARBONS. EFTS OF OVEREXP: TRACT), ABDOM PAIN. USED MOTOR OIL HAS BEEN SHOWN TO CAUSE SKIN CANCER IN LAB ANI MALS CONTINUALLY EXPOSED BY RPTD APPLICATIONS. AVOID PRLNGD/RPTD SKIN CONTACT.

=====
Physical/Chemical Properties
=====

B.P. Text: 425F,218C

Spec Gravity: 0.881 @ 60F

Evaporation Rate & Reference: SLOWER THAN ETHYL ETHER

Appearance and Odor: DRY, CLEAR AND BRIGHT LIQUID.

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: MAY FORM CARBON DIOXIDE & CARBON MONOXIDE, OXIDES OF SULFUR, NITROGEN & PHOSPHORUS, VARIOUS HYDROCARBONS.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

=====
Toxicological Information
==========
Ecological Information
=====

MSDS Transport Information

Regulatory Information

Other Information

HAZCOM Label

Product ID: NAPA MV MOTOR OIL SAE 10W30

Cage: G0029

Assigned IND: Y

Company Name: VALVOLINE INC

PO Box: 14000

City: LEXINGTON KY

Zipcode: 40512

Health Emergency Phone: 800-274-5263

Label Required IND: Y

Date Of Label Review: 03/03/1998

Status Code: C

Label Date: 03/03/1998

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Moderate

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. ACUTE: EYES MILD IRRITATION, STINGING, TEARING & REDNESS. SKIN: MILD IRRITATION. PROLONGED/REPEATED EXPOSURE MAY DRY SKIN WITH REDNESS, BURNING, DRYING AND CRACKING AND SKIN BURNS. INGESTION: SWALLOWING LARGE AMOUNTS MAY BE HARMFUL; GASTROINTESTINAL IRRITATION WITH NAUSEA, VOMITING, DIARRHEA. INHALATION: NOSE, THROAT, RESPIRATORY TRACT IRRITATION. CHRONIC: NONE LISTED BY MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.