MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This MISDS complies with OSHAS Hazard Com	IIIIuiiicatioii	Standard 29 CFK 191	0.1200 all	u OSHA FUIII	174		
IDENTITY AND MAN	UFACTU	RER'S INFORMATION	ON				
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special		HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B					
Manufactured For: UNISOURCE WORLDWIDE, INC.	DO	DOT Hazard Classification: ORM-D					
Address: 6600 Governors Lake Pkwy.	lder	Identity (trade name as used on label):					
Norcross, GA 30071		ALLSTAR SPOT SHOOTER (U17535)					
Phone: 800-UNISOURCE	MSI	MSDS Number: A00173 Revision -8					
		Date Prepared: 07/02/04 Prepared By: TR/IB Information Calls: (770) 422-2071					
SECTION 1 - MATERIAL II	DENTIFIC	ATION AND INFOR	MATION				
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **	
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
ISOPROPANOL		67-63-0	No	400	400	d	
2-BUTOXYETHANOL		111-76-2	Yes*	25 (skin)	20 (skin)	d	
ACETONE		67-64-1	No	1000	750	d	
PROPYLENE GLYCOL PHENYL ETHER		770-35-4	No	NE	NE	d	
DIPROPYLENE GLYCOL METHYL ETHER		34590-94-8	No	NE	NE	d	
*GLYCOL ETHER							
SECTION 2 - PHYSICAL	/CHEMIC	AI CHADACTEDI	L STICS				
Boiling Point: N/A				rate Only = 0	985		
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60		Specific Gravity (H2O=1): Concentrate Only = 0.985 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E						
Solubility in Water: Soluble Water Reactive: No							
Appearance and Odor: Clear spray with sweet fragrance.							
SECTION 3 - FIRE AN	ND EXPLO	OSION HAZARD DA	TA				
FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:							
(aerosols): 12 inch projection (not categorized as flammable) N/E % LEL: N/E % UEL: N/E							
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temper		ve 130°F or the contai	ner may ru	ıpture.			
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCC					T OCCUR		
Incompatibility (Mat. to avoid): Strong oxidizers Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and trace oxides of nitrogen.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS							
ACUTE EFFECTS Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Slight irritation. Skin Contact: Slight irritation. Prolonged contact increases irritation and skin absorption.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: Excessive and prolonged over- exposure may cause damage to nasal & respiratory passages, throat & esophagus. Lab animals have							
experienced anemia, liver, kidney, lung, blood damage to 2-butoxyethanol.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek r	medical at	ttention.					
Skin Contact: Remove contaminated clothing. Wash with soap	and wate	r. If irritated, seek n	nedical a	ttention. Lau	nder contan	ninated	
clothing before re-use.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glass	ses of wat	er. Get immediate	medical a	attention.			
SECTION 6 - CONTRO	L AND PR	ROTECTIVE MEASU	RES				
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH to be used in positive pressure mode.							
Protective Gloves: Disposable latex gloves suggested. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Stone To Be Taken If Material Is Smilled Or Peleased: Flush to sewer with water.							
Steps To Be Taken If Material Is Spilled Or Released: Flush to sewer with water. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.							