

# SAFETY DATA SHEET

## CLEAR PROTECTIVE LACQUER Aerosol

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME CLEAR PROTECTIVE LACQUER Aerosol  
PRODUCT NO. ECPL200H  
SUPPLIER ELECTROLUBE. A division of HK  
WENTWORTH LTD  
KINGSBURY PARK, MIDLAND ROAD  
SWADLINCOTE  
DERBYSHIRE, DE11 0AN  
UNITED KINGDOM  
+44(0)1283 222 111  
+44(0)1283 550 177

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTYL ACETATE -norm	204-658-1	123-86-4	10-30%	R10 R66 R67
DIMETHYL ETHER	204-065-8	115-10-6	30-60%	F+;R12
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

### 3 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

CLASSIFICATION Xi;R36. F+;R12. R67.

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention.

#### INGESTION

Not relevant.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

#### UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Ventilate well. Absorb in vermiculite, dry sand or earth and place into containers.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

**CLEAR PROTECTIVE LACQUER Aerosol****8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3

## PROTECTIVE EQUIPMENT



## ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

## RESPIRATORY EQUIPMENT

Suitable respiratory protection must be used at high concentrations.

## HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

## EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

## OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!**

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol Liquid		
COLOUR	Light brown		
ODOUR	Characteristic		
VOLATILITY DESCRIPTION	Volatile.		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	0.792 @ 20 °c	FLASH POINT (°C)	<0 CC (Closed cup).
AUTO IGNITION TEMPERATURE (°C)	425	FLAMMABILITY LIMIT - LOWER(%)	2.3
FLAMMABILITY LIMIT - UPPER(%)	12		

**10 STABILITY AND REACTIVITY**

## STABILITY

Stable under normal temperature conditions.

## CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalies.

**11 TOXICOLOGICAL INFORMATION**

## INHALATION

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

## SKIN CONTACT

Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin. Prolonged or repeated exposure may cause severe irritation.

## EYE CONTACT

Irritating to eyes.

## Other Health Effects

This substance has no evidence of carcinogenic properties.

## ROUTE OF ENTRY

Inhalation.

**CLEAR PROTECTIVE LACQUER Aerosol****12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

Not regarded as dangerous for the environment.

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2.1	ADR CLASS	Class 2.1: Flammable gases.
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	Not Applicable
EMS	F-D; S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
ICAO CLASS	2.1	AIR PACK GR.	Not Applicable

**15 REGULATORY INFORMATION**

## LABELLING



Irritant



Extremely Flammable

## RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S51	Use only in well-ventilated areas.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children

## UK REGULATORY REFERENCES

Chemicals (Hazard Information &amp; Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988.

## ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

## EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC. Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## CLEAR PROTECTIVE LACQUER Aerosol

### GUIDANCE NOTES

Workplace Exposure Limits EH40.

---

### 16 OTHER INFORMATION

---

#### REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

#### ISSUED BY

Helen O'Reilly

#### REVISION DATE

SEPTEMBER 2005

REV. NO./REPL. SDS GENERATED 2

#### SDS NO.

10341

#### RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

#### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.